

# TECHNICAL DATA SHEET

**5861 002 001 – 1000 ml**

**5861 002 300 – 300 ml**

**5861 002 150 – 150 ml**

## **Winter diesel performance improver**

To improve filterability and the cloud point of diesel fuel.

## **Fields of application:**

For all passenger car and truck diesel engines including common rail or unit injection systems. Manufacturer's specifications must be followed!

## **Properties:**

Improves filterability and the solidification point of diesel fuel. Suitable for all conventional diesel fuels but has no effect with pure bio-diesel. Ensures winter operation in cold conditions. Improvement of up to -10°C to -31°C in the best case, depending on the fuel quality.

## **Application:**

For better mixing, add to the fuel before refuelling.

Add 1000ml to achieve a concentration of 1:1000 in the fuel (concentrate).

Add 300ml to achieve a concentration of 1:500 in the fuel.

150 ml is sufficient for max. 70 l fuel.

## **Technical data:**

		Unit	Method
Appearance	Clear to cloudy		Visual inspection
Density at 20°C	0.83	g/cm <sup>3</sup>	DIN 51757
Flash point	63	°C	DIN ISO 2592
Odour	Characteristic		

## **Notes:**

The additive must be added before the first flocculation; the product cannot dissolve any flocculation that has already occurred. Ideally, the additive should be at room temperature and the diesel fuel

# TECHNICAL DATA SHEET

being treated should not be below 0°C. The additive should ideally be added just before the fuelling process.

This information is based on careful examinations and may be considered reliable. It serves to advise you and is without commitment on our part.

We provide this advice based on our own tests and experience and to the best of our knowledge. We assume no liability for the application results in individual cases, however, due to the large number of applications and the storage and application conditions that lie outside the scope of our influence.

This also applies to the use of the non-binding technical and commercial customer services provided by us. We always recommend that you conduct your own tests. We guarantee the consistent quality of our products. We reserve the right to make technical changes and to further develop our products.